

SUS-02-T SUS-02-T-Q

Ukazatel stavu

Level Indicator

Statusanzeiger



Montážní otvor ø16mm
Krytí IP65
Maximální proudový odběr 20mA
Faston 2,86mm x 0,8mm
Tloušťka panelu max. 8mm
Pracovní teplota -25.. +55°C

Mounting diameter ø16mm
Waterproof IP65
Maximal current consumption 20mA
Faston 2,86mm x 0,8mm
Panel thickness max. 8mm
Operating temperature -25.. +55°C

Montageloch ø16mm
Wasserdicht IP65
Max. derzeitiger Verbrauch 20mA
Faston 2,86mm x 0,8mm
Plattendicke max. 8mm
Arbeitstemperatur -25.. +55°C

Typ / Type / Typ	Provedení Design Design	LED 1	LED 2	LED 3	Napětí Voltage Spannung		Test Test Testen	
		Barva Colour Farbe	Barva Colour Farbe	Barva Colour Farbe	AC	DC	ne no nein ano yes ja	
<p>Rozteč mezi montážními otvory min. 25mm Spacing between mounting holes min. 25mm Abstand zwischen Montagelöchern mind. 25mm</p>	●	R	R	ne no nein	12V	AC DC	ne no nein	
	■ -Q	G	G		24V			
		B	B	R	48V			ano yes ja
		Y	Y	G	60V			
		W	W	B	110V			
		O	O	Y	125V			
				W	220V			
				O	230V			
					jiné other andere			

Příklad objednávky
Order example
Beispiel der Bestellspezifikation

SUS-02-T-R/G/O-110V-DC

SUS-02-T - R / G / O - 110V - DC -

V souladu s RoHS
RoHS compliant
RoHS konform